



MASH TL-2 Water Cable Barrier

MASH TL-2 Water Cable Barrier is a plastic, water filled portable barrier that provides positive protection to the work zone that redirects and brings the vehicle to a controlled stop, thus meeting the TL-1 and TL-2 requirements as a longitudinal Barrier under the Manual for Assessing Safety Hardware (MASH).

The MASH TL-2 uses water dispersion in combination with moulded-in steel cables. Upon impact, the plastic module ruptures and disperses the contained water to prevent vehicle intrusion into the work zone.

Simultaneously, the steel cables provide the strength to safely catch the misguided vehicle, preventing vehicle intrusion into the work zone.

FEATURES

- System is MASH compliant
- Steel cables provide added strength & safety
- Meets TL-1 & TL-2 requirements under MASH
- Each unit requires 466L of water
- Weight 45.6kg – empty
- Fill tabs – visual display
- A median or roadside barrier
- If end treatment required the **SLED Mini End Treatment** should be used.



Roadside



Workplace



Roadwork



Pedestrian






Seeing



Environment



Telecoms



ITEM NO.	DESCRIPTION
1	8" DIA WATER LEVEL INDICATOR
2	CONNECTION STEEL T-PIN
3	CIS FRAME
4	SLED MINI END TREATMENT

